

Features

- Cavity Duplexer for LTE Band 71.
- Very compact size and low weight. (86 x 123 x 65 mm)
- 1.0 dB typical Insertion loss @ room temp.
- 68 dB typical DL to UL Isolation.



Electrical Specifications

Duplexer DL Path (DL → ANT)

PARAMETER	SPECIFICATION	COMMENT
Frequency Range	663 MHz ~ 698 MHz	BW = 35 MHz
Insertion Loss	1.5 dB Max.	Over whole temp. range
Pass Band Ripple	1.0 dB Max.	
Return Loss	18.0 dB Min.	
Isolation	60.0 dB Min.	@ 617 MHz ~ 652 MHz
Max Power	100 Watts	CW
Impedance	50 Ω	

Duplexer UL Path (ANT → UL)

PARAMETER	SPECIFICATION	COMMENT
Frequency Range	617 MHz ~ 652 MHz	BW = 35 MHz
Insertion Loss	1.5 dB Max.	Over whole temp. range
Pass Band Ripple	1.0 dB Max.	
Return Loss	18.0 dB Min.	
Isolation	60.0 dB Min.	@ 663 MHz ~ 698 MHz
Impedance	50 Ω	

Environmental


Operating temperature range -20 to +70 °C

Mechanical

Dimensions¹⁾ 86 x 123 x 65 mm


1) Excluding connectors, and mounting bracket extension

Outline Drawing




Units : mm, Tolerance : +/- 0.2 mm

Typical Response



Duplexer DL path Transmission



Duplexer UL path Transmission